

Zenith Series ZR-10



Zenith Series ZR-10 Windows

The only commercially available, NFRC-certified full frame 0.10 U-factor window in North America.

Finally, the R10 window has arrived.

Window manufacturers have been working for decades to develop a commercially viable, full frame R10 window. Now, an industry leader has emerged with the only full frame certified R10 window on the market—Alpen High Performance Products.

Alpen's Zenith Series ZR-10 Features:

- ZR-10 high profile fixed window NFRC Certified to U-0.10 (R-10)
- Operable windows NFRC Certified to U-0.14 (R-7.1)
- Super-insulated energy efficient pultruded fiberglass frames
- Double film, triple chamber insulated glass assemblies featuring four independent low-e surfaces
- High-performance spacers and high-performance inert gas fill
- 99.5 % UV protection
- Extraordinary solar control with center of glass SHGC-0.18
- Proudly designed, developed and manufactured in the US



Zenith Series ZR-10



TECHNICAL SPECIFICATIONS



Zenith Series ZR-10 Full Frame NFRC Thermal Performance:

| ZR-10 | SolarControl | | | | Center-of-Glass | | | |
|--------------------------------------|-----------------|---------|------|------|-----------------|---------|------|------|
| | U-factor | R-value | SHGC | VT | U-factor | R-value | SHGC | VT |
| Fixed Low Profile Suspended Film | 0.11 | 9.1 | 0.19 | 0.44 | 0.06 | 16.7 | 0.18 | 0.38 |
| Fixed High Profile Suspended Film | 0.10 | 10.0 | 0.15 | 0.30 | 0.06 | 16.7 | 0.18 | 0.38 |
| Casement Suspended Film | 0.14 | 7.1 | 0.13 | 0.26 | 0.06 | 16.7 | 0.18 | 0.38 |
| Awning Suspended Film | 0.14 | 7.1 | 0.13 | 0.26 | 0.06 | 16.7 | 0.18 | 0.38 |
| Sliding Glass Door Suspended Film | 0.14 | 7.1 | 0.14 | 0.29 | 0.06 | 16.7 | 0.18 | 0.38 |

ALPENGLASS SOLARCONTROL ZR-10 FEATURES:

 $Double film, triple chamber insulated glass \ assemblies \ with four independent \ low-e \ surfaces \ results \ in$ maximum solar control and center-of-glass R-value 16.7

Ideal for cooling and heating dominated climates alike. Use with Alpen Zenith ZR-9 Series glazing to create whole-building with directionally-tuned performance.

WINDOW TYPES, TRIM ACCESSORIES & SIMULATED DIVIDED LIGHTS

Window Types

Fixed Low Profile (up to 68" x 72" or 48" x 96"), Fixed High Profile (up to 68" x 72" or 48" x 96"), Casement (up to 36" x 72"), Awning (up to 60" x 36"), Radius & Shapes, Custom Sizes, Sliding Patio Doors (2-, 3- and 4-panel options up to 16' x 8' overall), Mulled Window Walls (up to 96" x 105")

Trim Accessories

Exterior: Nailing Fin, Aluminum Brickmold, 3-1/4" and 2-5/8" Frame Extenders

Interior: Jamb Extensions: 4-9/16", 6-9/16", Pine, Oak and Fir

Simulated Divided Lights

Zenith Series ZR-10 windows offer interior and exterior-applied Simulated Divided Light (SDL) Grids in classic styles and custom patterns.

Interior: Interior grille matches interior paint and color.

Exterior (Aluminum): Exterior grille matches exterior paint color.

Contoured Grid Profile Widths: 7/8", 1-1/4" and 2"

Grid Styles: Colonial, Prairie, Double Prairie, Ladder, Faux Interlock

PAINT AND FINISH OPTIONS

Standard Colors: Casement, Awning, Picture Windows and Sliding Patio Doors



Hardware: Operable windows and Sliding Patio Doors

finish





