

## Zenith Sliding Glass Door



## **Bring the Outdoors Inside Without Sacrificing Performance**

Alpen's Zenith sliding glass doors bring the outdoors inside without sacrificing performance or comfort.

Slim, durable fiberglass frames provide minimal sight-line interference—amplifying views, daylight, and solar gain. Steel rollers allow you to move large super-insulated glass panels with ease.

### **Benefits:**

- NFRC performance ratings up to R-7.1.
- Exceeds Energy Star® Efficiency Standards.
- Superior air and water infiltration resistance.
- A durable, long-lasting, pultruded fiberglass frame provides high performance and style.
- Build your own doors with 14 standard painted finishes, split finish, and custom colors.
- Keyed multi-point locks deliver security with designer style.
- Get a full view, maximum daylight, and solar gain with clean, narrow line stile and rail design.
- Tested at a commercial-grade performance level for air and water infiltration resistance.



# **Zenith Sliding Glass Door**



### **TECHNICAL SPECIFICATIONS**

### **Representative of NFRC Certified Performance Ratings**

	Use	U-factor	R-value	SHGC	VT
ZR-6 Series Suspended Film	Balanced-6	0.19	5.3	0.26	0.43
	SolarControl-6	0.20	5.0	0.19	0.44
	HighGain-6	0.20	5.0	0.39	0.53
ZR-6 Series Thin Glass	Balanced-6 TGT	0.19	5.3	0.27	0.44
	SolarControl-6 TGT	0.19	5.3	0.19	0.44
	HighGain-6 TGT	0.19	5.3	0.44	0.54
ZR-9 Series Suspended Film	Balanced-9	0.19	6.3	0.24	0.38
	SolarControl-9	0.16	6.3	0.17	0.39
	HighGain-9	0.16	6.3	0.34	0.48
ZR-9 Series Thin Glass	Balanced-9 TGQ	0.14	7.1	0.25	0.41
	SolarControl-9 TGQ	0.14	7.1	0.18	0.41
	HighGain-9 TGQ	0.15	6.7	0.41	0.50

### **Standard Colors:**

Choose from 14 standard paint colors. Or match your home decor with custom color matching.



<sup>\*</sup>For a complete listing of color and style options, please see "Zenith Sliding Glass Door Color and Style Options" sheet.









### **Structural Performance Ratings**

Test Size	Performance Grade		
6068 2-Panel (OX, XO)	R- <b>50</b>		
12080 4-Panel (OXXO)	R-20		

O= Inoperable, X= Operable

### **Sizes & Configurations**

Two	Panel
	· anct

Min: 59-¼"-79-½" Max: 95-¼"-95-½"





### Three Panel

9068\* 12068

Min: 88-<sup>13</sup>/<sub>16</sub>" - 79-<sup>1</sup>/<sub>2</sub>" Max: 142-<sup>13</sup>/<sub>16</sub>" - 95-<sup>1</sup>/<sub>2</sub>"



XOC



ХОО



SXO

Min: 91-78" – 79-1/2" Max: 142-78" – 95-1/2"



### **Four Panel**

12068 16068

Min: 115-¾" – 79-½" Max: 187-¾" – 95-½"

